

Auto-Darkening Helmet <AS-4022F(D) Digital>

Cartridge <XA-5022D>



Adjustable Headgear : <HG-2002>

<HG-2003>



Features: -

- Use high quality LCD and multilayer optical interference filter, provides clear view and permanent UV/IR protection up to DIN 15.
- Power supply by solar cells, Lithium batteries (Replaceable).
- Helmet Shell made of high impact resistant Polyamide Nylon.
- Ample mask space, especially for ears and bottom flare for neck protection.
- Filter meets ANSI Z87.1, CSA Z94.3.
- Helmet Shell meets ANSI Z87.1, CSA Z94.3, EN ISO 16321.

Technical Specifications: -

ADF Cartridge Size	114 x 133 x 9.5mm (4-1/2" x 5-1/4" x 3/8")
LCD Viewing area	100 x 60mm (3.94" x 2.36")
Light State Shade	DIN 4
Dark Variable Shades	DIN 5-9 / 9-13 <digital control>
UV/IR Protection	Up to DIN 15 at all times
Switching time (light to dark)	0.08ms
Delay Time (dark to light)	Adjustable (1-5 for 0.1-0.9s) <digital control>
Sensitivity	Adjustable (1-5 for low-high) <digital control>
Arc Sensors	4
Grind Function	Yes, digital control
Low Amp TIG Adapted	Yes, from 3 Amp
Power Supply	Solar cell and 2 CR2450 batteries
Operation Temperature	-10°C~65°C (14°F~149°F)
Storage Temperature	-20°C~85°C (-4°F~185°F)
Inside PC lens	106 x 66 x 1mm (4.17" x 2.60")
Outside PC lens	114 x 133 x 1mm (4-1/2" x 5-1/4")
Mag Lens slot	Yes
Color	Black, Blue, Iron Grey
Weight	555g
Warranty	2 years

Packing: -

- Each with a color box, 14 pieces in a carton
- 1 manual per helmet

GRACEDUTY COMPANY LIMITED

Room 1102 - 1104, 11/F., CRE Centre,
889 Cheung Sha Wan Road, Kowloon, Hong Kong, China
Tel: (852) 2420-5808 (6 Lines) Fax: (852) 2420-5507
E-mail : welding@graceduty.com.hk <http://www.graceduty.com.hk>